

## Data Sheet and Build Recommendation

### SM560 | 11L Mini-ITX PC Case for full length 3-slot GPUs



- + Supports Mini-ITX motherboards
- + Front panel with USB 3.1 Type C (SS+ 10 Gbit/s), USB 3.0 Type A, and Dual Audio Jacks
- + Supports triple slot GPUs up to 305mm long x 155mm tall
- + Compatible with air coolers up to 55mm tall, or some larger coolers with fan removed
- + Support SFX and SFX-L form factor power supplies
- + Mounts two 120mm x 25mm thick fans in bottom for high performance cooling
- + Magnetic dust filters available from [Demcifilter](#)
- + Designed and manufactured in the USA by [Sliger](#)



Technical Specifications	
<b>Motherboard</b>	Mini-ITX (170 x 170mm)
<b>CPU Air Coolers</b>	Maximum of 55mm tall CPU coolers Coolers that require a Vented Side Panel on the CPU side ID-COOLING IS-60 (55mm) AMD Wraith Stealth (54mm) Cooltek LP53 (53mm) Coolers compatible with all side panel types (Unvented, Window, or Vented) Alpenföhn® Black Ridge (47mm) Noctua L9i/L9a Intel Boxed Cooler Cryorig C7 CU Cryorig C7 Cooltek ITX30 Phanteks PH-TC90LS RAIJINTEK Zelos Silverstone AR05

	Silverstone AR11 SEMI-PASSIVE MODE: these heatsinks require Unvented or Window panels, and two high static pressure fans be quiet! SHADOW ROCK LP (FAN REMOVED) Phanteks PH-TC12LS (FAN REMOVED) Noctua NH-L9x65 (FAN REMOVED) REEVEN BRONTES RC-1001b (FAN REMOVED) Scythe SCSK-1100 Shuriken Rev. B (FAN REMOVED) SCYTHE Big Shuriken 3 CPU Cooler SCBSK-3000 (FAN REMOVED) Thermalright AXP-100H Muscle (FAN REMOVED) Thermalright AXP-100 Copper (FAN REMOVED) Cooltek CR-701 (FAN REMOVED)
<b>AIO Liquid Cooler</b>	92mm Asetek 645LT Requires 92mm AIO adapter plate 120mm AIO liquid coolers Requires 120mm AIO kit 120mm radiator thickness + 120mm fan thickness must be < 72mm CPU pump block / coolant hoses must be < 55mm tall from CPU Limits GPU length to 187mm long
<b>Fan Mounting</b>	2x 120mm fans in bottom plenum Fans can be a maximum of 25mm thick with high static pressure on the bottom as intake
<b>PCIe Cards</b>	Supports three(3) slot wide cards with room between side panel and card for airflow Card is mounted behind motherboard on a PCIe 3.0 16x Flexible Ribbon Riser with 120mm AIO kit Maximum card length: 187mm with Standard Inlet Maximum card height: 133mm (157mm for power connectors) Maximum card length: 305mm (325mm with front panel SSD tray removed) Maximum card width: 67mm with Pigtail Inlet Maximum card height: 157mm Maximum card length: 305mm (325mm with front panel SSD tray removed) Maximum card width: 67mm We recommend to measure components yourself to avoid incompatibility caused by manufacturers discrepancies in dimensions
<b>Storage</b>	(2x) 2.5" SSD/HDD mounting points behind front panel Optional (4x) 2.5" SSD/HDD mounting bracket [replaces 1x 120mm bottom fan] Maximum two brackets for total of 8x 2.5" SSD/HDDs Optional (1x) 3.5" HDD mount bracket [replaces 1x 120mm bottom fan] Maximum two brackets for (2x) 3.5" HDD in bottom of case
<b>Front connection</b>	One USB 3.1 Gen 2 Type C to USB E header (SS+ 10 Gbit/s) One USB 3.0 Type A to 20-Pin Motherboard Header Two Audio Jacks to standard 9-Pin HD AUDIO header
<b>Security</b>	1x Kensington Lock Cutout
<b>Power Supply</b>	SFX Corsair SF series SilverStone SST-SX series

	EVGA SuperNOVA GM series FSP Dagger series SFX-L is supported; however, it is a very tight fit and not recommended. Sliger recommends a fan guard grill or custom cables if you do go with SFX-L. It is recommended to mount your PSU with the fan intake facing the GPU for best thermals.
<b>Material</b>	Chassis: Galvanized Steel Side Panels: Aluminum Sheet Feet: Black SBR
<b>Finish</b>	Powder coated coating
<b>Outside Dimensions</b>	335mm x 159mm x 208mm (LxWxH)
<b>Weight</b>	3.80 kg (Base configuration)
<b>Rev. Control</b>	<b>SM560-A (3/1/19 - 6/14/19)</b> Initial Release <b>SM560-B (6/15/19 - X/XX/XX)</b> Modified vent pattern to match SM550 vent style Added perforations around motherboard IO shield for better semi-passive mode cooling

Info	
Manufacturer	Importer

**SLIGER**

Sliger Designs Inc.  
 1575 Linda Way, Suite 107  
 Sparks, NV 89431, USA  
 +1 775 356 5595a  
[www.sliger.com](http://www.sliger.com)



**DENSITY LABS s.r.o.**  
 Veterná ulica 759/37  
 SK-90067 Láb, Slovakia  
[www.DENSITY.sk](http://www.DENSITY.sk)



Sliger Designs Inc. and Density Labs s.r.o. declare that this equipment is in compliance with Low Voltage Directive 2014/34/EU according to the standard EN 62368-1:2014. Copy of the original declaration may be obtained at [info@density.sk](mailto:info@density.sk).

© 2019 Density Labs s.r.o. and Sliger Designs Inc. All rights reserved. DENSITY logo is a property of Density Labs s.r.o. in Slovakia and/or in other countries. All other trademarks are the property of their respective owners. Product may vary slightly from pictures in this document. Specifications and/or features may be subject to change without prior notice.